



SOIL CULTIVATION MACHINERY

MINI ROTARY TILLER

- Wide range of models
- Strong, robust and durable body structure
- Long-lasting imported blades
- Long service life thanks to friction type clutch system
- Extensive and experienced service network
- Spare parts availability
- 2 years of warranty



Hisarlar Tarım Makineleri

Erkunt Traktör Sanayii A.Ş.
Organize Sanayi Bölgesi Batı Hun Cad. No:2
06935 Sincan Ankara/TÜRKİYE

hisarlartarimmakineleri.com.tr
hisarlaryedekparca.com.tr



0312 267 50 00



Mini Rotary Tiller

- The friction type clutch system used in Mini Rotary Tiller models prevents sudden loads from the tractor during the engagement of the PTO shaft from damaging the transmission. This ensures long-lasting and safe operation.

- With the hydraulic sliding system offered on the Hydraulic Slide Mini Rotary Tillers, the operator can slide the machine into the area between the trees, ensuring a flawless plowing without leaving any unworked area.

- It easily breaks up and quickly mixes the soil with blades designed in the best form and arrangement. Due to the strong and robust blades, it is possible to work successfully in all kinds of soil conditions.



The friction type clutch system used in Mini Rotary Tillers prevents sudden loads from the tractor during the engagement of the PTO shaft from damaging the transmission. This ensures long-lasting and safe operation.



In the Mini Rotary Tiller models, there are skid feet that adjust the depth of penetration of the Rotovator in the soil.

TECHNICAL SPECIFICATIONS						
MODEL	WORK WIDTH (CM)	WORK DEPTH (CM)	NUMBER OF BLADES AND FLANGES	REQUIRED TRACTOR POWER (HP)	WEIGHT CAGE ROLLER (KG)	MACHINE DIMENSIONS (W x L x H) (CM)
85 FIXED MINI ROTARY TILLER	79	15	18/4	20-25	220	79x100x105
105 FIXED MINI ROTARY TILLER	102	15	24/5	25-30	325	79x118x105
125 FIXED MINI ROTARY TILLER	125	15	30/6	30-40	330	79x140x105
145 FIXED MINI ROTARY TILLER	148	15	36/7	40-450	345	79x165x105
105 HK MINI ROTARY TILLER	102	15	24/5	25-30	330	96x115x105
125 HK MINI ROTARY TILLER	125	15	30/6	30-40	335	96x135x105
145 HK MINI ROTARY TILLER	148	15	36/7	40-50	350	96x160x105

*Hisarlar Tarım Makineleri reserves the right to make changes to the machines without prior notice and without making changes to previously sold machines.



Due to the hydraulic sliding system offered in Hydraulic Slide Mini Rotary Tillers, the operator moves the machine away from barriers without getting off the tractor, thus providing a safe and comfortable working opportunity.



With the adjustable spring-loaded cover opening provided as standard, the soil chopping size can be adjusted.



“C” Blade Form

Mini Rotary Tillers offer C blade form as standard, which enables more efficient operation in moist and soft type soils.