



SOIL CULTIVATION MACHINERY

ORCHARD TYPE ROTARY TILLERS

- Wide variety of models
- Strong, robust and durable body structure
- Long-lasting imported blades
- Standard gear type power transmission
- Long service life due to friction type clutch system
- Extensive and experienced service network
- Spare parts availability
- 2 years of warranty



Hisarlar Tarım Makineleri

Erkunt Traktör Sanayii A.Ş.
Organize Sanayi Bölgesi Batı Hun Cad. No:2
06935 Sincan Ankara/TÜRKİYE

hisarlartarimmakineleri.com.tr
hisarlaryedekparca.com.tr



0312 267 50 00



Orchard Type Rotary Tillers

Orchard Type Rotary Tillers with Sensors are designed to easily work between the trees in orchards. When any barrier is encountered during operation, all barriers are automatically overcome by means of the piston activated by the sensor system, providing the operator with a convenient and comfortable working opportunity.

With the hydraulic shift system offered in the Hydraulic Shift Orchard Type Rotary Tillers models, the operator can shift the machine to the area between the trees without getting off the tractor, ensuring a perfect plowing without leaving any untouched surface. This provides long hours of comfortable use.

The soil is easily broken up and mixed due to the high-strength and optimally shaped blades.



With the friction type clutch system used in Orchard Type Rotary Tillers models, sudden movements from the tractor are prevented from damaging the transmission. In this way, a long-lasting use is provided to the user.



In Orchard Type Rotary Tillers, L blade form, which enables more efficient operation in dry and rigid soils, and C blade form, which enables more efficient operation in moist and soft type soils, are optionally available.



TECHNICAL SPECIFICATIONS						
MODEL	WORK WIDTH (CM)	WORK DEPTH (CM)	NUMBER OF BLADES AND FLANGES	REQUIRED TRACTOR POWER (HP)	WEIGHT WITH PACKER ROLLER (KG)	MACHINE DIMENSIONS (W x L x H) (CM)
1600 FIXED	160	20	36 / 7	40 - 55	415	85 x 175 x 105
1800 FIXED	180	20	42 / 8	55 - 65	455	85 x 200 x 105
1800 FIXED 4 V	180	20	42 / 8	55 - 65	480	85 x 200 x 105
2100 FIXED	210	20	48 / 9	65 - 75	510	85 x 225 x 105
2100 FIXED 4 V	210	20	48 / 9	65 - 75	530	85 x 225 x 105
2400 FIXED	240	20	54 / 10	70 - 85	565	85 x 245 x 105
2400 FIXED 4 V	240	20	54 / 10	70 - 85	575	85 x 245 x 105
1800 HYDRAULIC SHIFT	180	20	42 / 8	55 - 65	620	120 x 200 x 120
1800 HYDRAULIC SHIFT 4 V	180	20	42 / 8	55 - 65	630	120 x 200 x 120
2100 HYDRAULIC SHIFT	210	20	48 / 9	65 - 75	655	120 x 225 x 120
2100 HYDRAULIC SHIFT 4V	210	20	48 / 9	65 - 75	665	120 x 225 x 120
2400 HYDRAULIC SHIFT	240	20	54 / 10	75 - 90	680	120 x 252 x 120
2100 WITH SENSOR	210	20	48 / 9	65 - 75	725	120 x 232 x 120

*Hisarlar Tarım Makineleri reserves the right to make changes to the machines without prior notice and without making changes to previously sold machines.

OPTIONAL FEATURES



The size of the soil chop can be adjusted due to the spring-loaded adjustable cover opening provided as standard.



Wheel

Skid

Orchard Type Rotary Tillers are available with skid and wheeled models as options.



The 4-speed gearbox, which is offered as an alternative to the single-speed gearbox in Orchard Type Rotary Tillers, provides a more efficient use and an efficient work result in different soil conditions.