



HAY & FORAGE EQUIPMENT

SMALL SQUARE BALER

- Low fuel consumption
- Heavy-duty chassis
- Powerful feeding chamber
- Hydraulic road-work position
- Dense baling ability
- High performance collector unit
- Well-Known German Raspe brand binding group
- Spare parts availability
- 2 years of warranty



Hisarlar Tarım Makineleri

Erkunt Traktör Sanayii A.Ş.
Organize Sanayi Bölgesi Batı Hun Cad. No:2
06935 Sincan Ankara/TÜRKİYE

hisarlartarimmakineleri.com.tr
hisarlaryedekparca.com.tr



0312 267 50 00



Small Square Baler

- The most important thing to consider when buying a baler is the bale density, which determines the amount of products in the bale. Another important consideration is the weight of the bales made in terms of transportation and storage efficiency.

- Small balers offered for users with heavy-duty 2-twine and 3-twine non-chopper models, and with 3 different options such as digital bale counter, third support wheel and picker wheel needed on rough surfaces, are designed for minimizing product losses and increasing your productivity due to the high-capacity collector unit.

- A water tank and fire extinguisher are available as standard on the small square baler.



High-performance collecting unit; With the collecting unit equipped with powerful collecting fingers, no uncollected crop is left in the field.



Hydraulic road-work position; Controlled from the cab via hydraulic joysticks, the road-work position adjustment provides comfort and easy operation.

TECHNICAL SPECIFICATIONS	SB 263	SB 363
BALE CHAMBER DIMENSIONS		
WIDTH (CM)	46	46
HEIGHT (CM)	36	36
LENGTH (CM)	30-140 adjustable	30-140 adjustable
COLLECTOR ASSEMBLY		
CONTROLLER TYPE	Hydraulic	Hydraulic
WIDTH (INSIDE) (CM)	163	163
NUMBER OF FINGERS (PCS)	Over five bars, 110 pcs	Over five bars, 110 pcs
PISTON		
SPEED (STROKES/MIN)	92-104	92-104
BINDING SYSTEM		
RASSPE		
BINDING TYPE, NUMBER OF TWINES (PCS)	Knotting, 2	Knotting, 3
BINDING GROUP FANS	Standard	Standard
ROLLER CAPACITY (PCS)	8	8
BINDING GROUP LUBRICATION	Manual Grease Holder	Manual Grease Holder
TRACTOR POWER REQUIREMENT		
MIN. TRACTOR POWER REQUIREMENT (HP)	70	70
PTO SPEED (R/MIN)	540	540
MACHINE DIMENSIONS		
HEIGHT (CM)	188	188
WIDTH (CM)	253	253
LENGTH (CM)	553	553
MACHINE WEIGHT (KG)	2.000	2,020

*Hisarlar Tarım Makineleri reserves the right to make changes to the machines without prior notice and without making changes to previously sold machines.



Twine Chamber

Long-term uninterrupted working opportunity due to the cabinet with a capacity of 8 twine reels.



Binding Group

High capacity operation with the well-known German RASSPE brand binding group.



Heavy and Powerful Flywheel

Does not force the tractor with its own rotation effect after the machine takes the first rotation movement and offers low fuel consumption.